

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problems Mailbox.**

THIS PAGE BLANK (USPTO)



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : G11B 27/32, 20/12, 27/10	A1	(11) International Publication Number: WO 00/14744 (43) International Publication Date: 16 March 2000 (16.03.00)																
<div style="display: flex; justify-content: space-between;"> <div style="width: 48%;"> (21) International Application Number: PCT/EP99/06377 (22) International Filing Date: 30 August 1999 (30.08.99) (30) Priority Data: <table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 30%;">98250315.3</td> <td style="width: 40%;">7 September 1998 (07.09.98)</td> <td style="width: 30%;">EP</td> </tr> <tr> <td>98250387.2</td> <td>4 November 1998 (04.11.98)</td> <td>EP</td> </tr> <tr> <td>99250179.1</td> <td>8 June 1999 (08.06.99)</td> <td>EP</td> </tr> <tr> <td>99250214.6</td> <td>1 July 1999 (01.07.99)</td> <td>EP</td> </tr> </table> (71) Applicant (for all designated States except US): DEUTSCHE THOMSON-BRANDT GMBH [DE/DE]; Hermann-Schwer-Strasse 3, D-78048 Villin- gen-Schwenningen (DE). (72) Inventors; and (75) Inventors/Applicants (for US only): SCHILLER, Harald [DE/DE]; Apfelgarten 11, D-30539 Hannover (DE). KEESEN, Heinz-Werner [DE/DE]; Siemensstrasse 22, D-30173 Hannover (DE). WINTER, Marco [DE/DE]; Böhmerstrasse 17, D-30173 Hannover (DE). (74) Agent: HARTNACK, Wolfgang; Deutsche Thom- son-Brandt GmbH, Licensing & Intellectual Property, Karl-Wiechert-Allee 74, D-30625 Hannover (DE). </div> <div style="width: 48%;"> (81) Designated States: AL, AM, AU, AZ, BA, BB, BG, BR, BY, CA, CN, CU, CZ, EE, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, RO, RU, SD, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i> </div> </div>			98250315.3	7 September 1998 (07.09.98)	EP	98250387.2	4 November 1998 (04.11.98)	EP	99250179.1	8 June 1999 (08.06.99)	EP	99250214.6	1 July 1999 (01.07.99)	EP				
98250315.3	7 September 1998 (07.09.98)	EP																
98250387.2	4 November 1998 (04.11.98)	EP																
99250179.1	8 June 1999 (08.06.99)	EP																
99250214.6	1 July 1999 (01.07.99)	EP																
(54) Title: METHOD FOR ADDRESSING A BITSTREAM RECORDING (57) Abstract <div style="display: flex;"> <div style="width: 35%;"> <p>In bitstream recording presentation data is organised into Video Object Units. These have a variable size but have also a variable duration. To allow access to any Video Object Unit in the bitstream a mapping list is used which is based on pieces (SOBU#n) of the bitstream of constant size per piece. The mapping list additionally contains for each of these pieces a specific delta duration (IAPAT#n) which indicates the difference between the arrival time of the first packet of a piece and the arrival time of the packet following immediately the last packet of that piece, and contains an initialisation value (IAPAT#0) which allows to have a share of equal bits between a predetermined amount of MSBs of application time stamps (ATS) and the same amount of LSBs of the summation of said delta time durations (IAPAT#n).</p> </div> <div style="width: 60%; text-align: center;"> <table border="1" style="margin: auto; border-collapse: collapse;"> <tr><td style="padding: 5px;">SOBU#n</td><td style="padding: 5px;"></td></tr> <tr><td style="padding: 5px;">SOBU#n-1</td><td style="padding: 5px;">IAPAT#n-1</td></tr> <tr><td style="padding: 5px;">SOBU#i</td><td style="padding: 5px;">IAPAT#i</td></tr> <tr><td style="padding: 5px;"></td><td style="padding: 5px;"></td></tr> <tr><td style="padding: 5px;">SOBU#3</td><td style="padding: 5px;">IAPAT#3</td></tr> <tr><td style="padding: 5px;">SOBU#2</td><td style="padding: 5px;">IAPAT#2</td></tr> <tr><td style="padding: 5px;">SOBU#1</td><td style="padding: 5px;">IAPAT#1</td></tr> <tr><td style="padding: 5px;"></td><td style="padding: 5px;">IAPAT#0</td></tr> </table> </div> </div>			SOBU#n		SOBU#n-1	IAPAT#n-1	SOBU#i	IAPAT#i			SOBU#3	IAPAT#3	SOBU#2	IAPAT#2	SOBU#1	IAPAT#1		IAPAT#0
SOBU#n																		
SOBU#n-1	IAPAT#n-1																	
SOBU#i	IAPAT#i																	
SOBU#3	IAPAT#3																	
SOBU#2	IAPAT#2																	
SOBU#1	IAPAT#1																	
	IAPAT#0																	

DAV →

SOBU#n	
SOBU#n-1	IAPAT#n-1
SOBU#i	IAPAT#i
SOBU#3	IAPAT#3
SOBU#2	IAPAT#2
SOBU#1	IAPAT#1
	IAPAT#0

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

METHOD FOR ADDRESSING A BITSTREAM RECORDING

The invention relates to a method and to an apparatus for
5 addressing a bitstream to be recorded or being recorded on a
storage medium, e.g. an optical disc.

Background

10 In bitstream recording one is free to subdivide the bit-
stream into sub-units of more regular structure. Presenta-
tion data in DVDs (digital video or versatile disc) is or-
ganised into units called Video Object Unit, denoted VOBU,
15 or Stream Object Unit, denoted SOBU, e.g. in the DVD VR
Specification for DVD Video Recording in which the units are
called VOBUs. VOBUs have a variable size (data amount meas-
ured in number of sectors), but have also a variable dura-
tion (measured in number of video fields). SOBUs have a con-
20 stant size, but have also a variable duration.

For data retrieval from the disc the DVD VR specification
foresees a 'VOBU map' which is a table where for every VOBU
in a recording the length in sectors and the duration in
fields is entered.

Invention

A table for data retrieval from a storage medium can be
30 based on bitstream data being subdivided into pieces of con-
stant duration. 'Duration' means the difference between the
arrival time of the first packet of a piece and the arrival
time of the packet following immediately the last packet of
that piece.

35 'Housekeeping' in the general context of either DVD VR re-
cording or Stream recording is the task to translate a given

time value (presentation time in case of DVD VR recording or packet arrival time in case of Stream recording) into a disc address value where the desired data can be found.

In such systems the VOB or SOBU map or 'mapping list', denoted MAPL, can contain a specific size or a specific offset or a specific delta size or, in general, a specific address-like quantity for each of these constant-duration pieces. By storing delta values instead of the total duration at a current VOB or SOBU these entries can be described with shorter word length which helps to keep the total MAPL in a reasonable size.

A possible type of housekeeping process for these systems could include the following steps:

- By division and truncation, calculate from the given time value the index of the mapping list entry to be looked up.
- The content of the mapping list entry either directly specifies the address value to access, or all mapping list entries up to that index have to be accumulated to get the address value to be accessed.

The big disadvantage of such type of MAPL which is based on constant-duration pieces lies in the following:

- In case of a low bitrate recording the pieces of constant duration will be small in size, i.e. every piece will comprise a few data sectors only or, in the extreme, a fraction of a data sector only. The disc can contain enormous numbers of those pieces, so that the MAPL may become too big to be kept in the memory.
- In case of high bitrate recording, the pieces of constant duration are big in size, i.e. each piece will comprise many data sectors. Then, addressing one piece or another corresponds to a very coarse addressing on the (sector) scale, i.e. a piece address derived from the MAPL can be located many sectors away from the currently desired location.

Therefore housekeeping based on constant-duration pieces can result in a too big MAPL in some cases (up to one half of the disc capacity), and can result in too coarse addressing in other cases.

5 It is one object of the invention to disclose a method for assigning to a given time value a storage medium address value which method avoids such disadvantages. This object is achieved by the method disclosed in claim 1.

10 According to the invention the mapping list MAPL is based on pieces of constant length or size, i.e. a constant number of bits per piece.

In a medium like DVD-RAM where data are physically organised into 'ECC blocks' (ECC: error correction code) of 32kByte
15 length each, particular advantages result if the above constant size or a multiple of it is used as the constant size of a piece. However, any other constant size can be used. In this case of pieces of constant size the MAPL contains for each of these pieces of constant size a specific absolute
20 duration or, preferably, a specific delta duration which indicates the arrival time of the first packet of a piece and the arrival time of the packet following immediately the last packet of that piece.

The housekeeping process, i.e. the computation of the target
25 VOB or SOBU address includes the following steps:

- Accumulate the delta durations contained in the MAPL until the given time value is most closely reached towards the target VOB or SOBU, i.e. until the sum of delta durations is less than or equal to the given time value and
30 the result after addition of the next delta duration is greater than the given time value assuming that forward scanning of the VOB or SOBU entries is performed, or until the sum of delta durations is greater than the given time value assuming that backward scanning of the VOB or
35 SOBU entries is performed.
- The running index of this mapping list entry multiplied

by the constant piece size directly results in the address value to be accessed.

The advantages of the inventive constant-size based MAPL are:

- the MAPL size does not depend on the bitrate of the recordings,
- the MAPL addressing accuracy is constant, the granularity basically corresponds to the 'piece size constant' which can be chosen as appropriate to be constant for all types of discs, to be constant per disc, or to be constant per recording on a specific disc.

Advantageously, the address table contains an additional initialising value to initialise the accumulation of the delta time durations.

In principle, the inventive method is suited for addressing a bitstream to be recorded or being recorded on a storage medium, e.g. a DVD recorder, wherein an address table is used that is based on pieces of said bitstream, and wherein:

- said pieces each include a constant amount of bits of said bitstream;
- using a running index, to each address table entry for said pieces, in particular to each address table entry except the one having the highest index, a delta time duration is assigned in said address table;
- the address table contains in addition an initialisation value which allows to have a share of equal bits between a predetermined amount of MSBs of application time stamps and the same amount of LSBs of said delta time durations;
- in order to get an address value for reaching a target address said initialisation value and all delta time durations up to the nearest time duration corresponding to said address value become accumulated and the running index corresponding to the delta time duration entry related to said nearest time duration becomes multiplied by

said constant amount in order to compute said address value.

Advantageous additional embodiments of the inventive method
5 are disclosed in the respective dependent claims.

Drawings

- 10 Embodiments of the invention are described with reference to the accompanying drawings, which show in:
- Fig. 1 simplified overall system for DVD Stream Recording;
 - Fig. 2 basic directory and file structure;
 - Fig. 3 navigation data structure;
 - 15 Fig. 4 a stream pack;
 - Fig. 5 inventive mapping list;
 - Fig. 6 structure of this mapping list;
 - Fig. 7 mapping list example;
 - Fig. 8 comparison of several time values;
 - 20 Fig. 9 IAPAT structure;
 - Fig. 10 APAT and PAT structure;
 - Fig. 11 ATS structure.

25 Exemplary embodiments

The DVD VR stream recording system is designed to use rewritable DVD discs for recording existing digital bitstreams, editing them and playing them back as bitstreams.

30 The following abbreviations are used:

AP: Application Packet, APAT: Application Packet Arrival Time, ATS: Application Timestamp, IAPAT: Incremental APAT (delta values with 12 bit resolution), LB: Logical Block,
35 LSBs: least significant bits, MAPL: Mapping List, MSBs: most significant bits, MTU_SHFT: Mapping Time Unit Shift (an un-

signed integer value, e.g. 18), PAT: Packet Arrival Time, RBN: relative byte number, RBP: relative byte position, RLBN: relative logical block number, SCR: system clock reference, SOB: Stream Object, SOBU: Stream Object Unit,

5 SOB_E_APAT: APAT of the last AP of the SOB, SOB_S_APAT: APAT of the first AP of the SOB, SOBU_S_APAT: APAT of the first AP of the SOBU, STB: set top box, SUM_IAPAT = Summation of IAPAT values, TOC: table of content.

10 This system is designed to satisfy the following requirements:

A timing mechanism, i.e. a time stamp is added to every broadcast packet to enable proper packet delivery during playback.

15 To enlarge the fields of applications, non-real-time recording should be possible. However, in this case the STB has to generate the Time Stamp information.

Data allocation strategy and file support real-time stream recording.

20 Many digital services require Service Information which normally is embedded in the real-time stream. To support a STB fed by data from a DVD player, the DVD should provide additional space, which can be used by the STB to duplicate part of the service information and to add additional TOC information.

25 Copy Protection must be supported. In addition, any scrambling performed by the service provider or the STB must be kept unchanged.

User requirements can be grouped into requirements for recording, requirements for playback, and requirements for editing:

Real-time Recording

35 The system should be designed to enable real-time recording of digital streams. It also should allow the user to concatenate recordings, even if those recordings consist of different stream formats. If recordings are concatenated, a

seamless or close to seamless playback possibility would be nice but is not required.

Navigation Support

- 5 To support navigation two pieces of information (lists) should be generated during recording:
- 1) An 'original' version of a play list. This list contains quite low level information, e.g. time map or (broadcast) packet order of the recording. This list is accessible by
10 the STB and the content is understood by the DVD streamer as well as by the STB. In its original version the playlist enables the playback of a complete recording. The playlist may be accessed and extended after recording by the STB to allow more sophisticated playback sequences.
 - 15 2) The second piece of information, a mapping list, is generated to support the stream recorder to retrieve packet stream chunks (cells), that are described in terms of the application domain, e.g. 'broadcast packets' or 'time'. This list is owned and understood by the DVD streamer only.

20

Content Description

- The system should reserve space which can be used by the STB to store high level TOC and Service Information. This information is provided for the user to navigate through the content stored on disc and may contain sophisticated GUI information.
25 The content needs not to be understood by the stream recorder. However a common subset of the TOC information, e.g. based on a character string, may be useful to be shared between STB and DVD, in order to enable the stream recorder
30 to provide a basic menu by itself.

Playback of individual recording and playing all recordings sequentially should be possible via play list.

35 Player menus for entry point selection

The STB can generate a sophisticated menu based on the TOC

information stored on the disc. However, it should be possible to generate a simple menu by the streamer itself, e.g. via some 'character' information which is shared by STB and DVD.

5

Trick play modes

The STB should be able to steer trick play via the 'play list'. Due to the nature of the broadcast stream, the trick play features may be limited to basic ones, e.g. Time Search and Title Jump.

User defined playback sequence features like programming or parental control can be supported via the play list

The DVD streamer should create the 'original version' of the play list. It also should allow extensions and modifications of the play list by the STB for more sophisticated playback features. The DVD streamer is not responsible for the content of those sophisticated playlist(s).

The system must support the deletion of single recordings on user's request. If possible, the system should allow this feature under the control of the STB.
The system may support insert editing.

In the simplified overall system of Fig. 1 an application device AD interacts via an interface IF, e.g. an IEEE1394 interface, with a streamer device STRD, i.e. a DVD recorder. A streamer STR within STRD sends its data via output buffering & timestamping handling means BTHO to IF and receives from IF data via input buffering & timestamping handling means BTHI. AD sends its data via output buffering & timestamping handling means BTHOAD to IF and receives from IF data via input buffering & timestamping handling means BTHIAD.

Concerning the directory and file structure, the organisation of Stream Data and Navigation Data of DVD Stream Re-

cording is done in a specific way such as to take into account the following:

- Any DVD Streamer device STRD has certain requirements to store its own mapping list or Streamer-specific navigation data on the disc. These data are solely for helping the retrieval of recorded data; they need not be understood or even be visible to any outside application device AD.
- Any DVD Streamer device STRD needs to communicate with the application device AD it is connected to. This communication should be as universal as possible so that the maximum possible range of applications can be connected to the Streamer. The Navigation Data to support such communication are called Common navigation data and must be understandable by the Streamer as well as by the application device.
- The Streamer device STRD should offer to the connected application device AD a means for storing its own private data of any desired kind. The Streamer needs not to understand any of the content, internal structure, or meaning of this Application-specific navigation data.

Fig. 2 illustrates a possible directory and file structure where all the data comprising the disc content are. The files storing the disc content are placed under the STRREC directory which is under the root directory. Under the STRREC directory the following files are created:

- COMMON.IFO
Basic information to describe the stream content. Needs to be understood by the Application Device as well as the Streamer.
- STREAMER.IFO
Private stream object information specific to the Streamer Device. Needs not to be understood by the Application Device.
- APPLICAT.IFO

Application Private Data, i.e. information that is specific to the Application(s) connected to the Streamer. Needs not to be understood by the Streamer.

- REALTIME.SOB

5 Recorded real-time stream data proper.

Note that except for the files described above, the STRREC directory shall not contain any other files or directories.

Concerning the navigation data structure, Navigation data is provided to control the recording, playing back, and editing of any bitstreams that are recorded. As shown in Fig. 3, Navigation Data includes Streamer Video Manager Information (STR_VMGI) as contained in the file named COMMON.IFO and Stream File Information (SFI) as contained in the file named
10 STREAMER.IFO. From the point of view of the Streamer Device, these two kinds of information are sufficient to perform all necessary operations.

In addition to these, DVD Stream Recording also foresees the possibility of reserving a storage location for Application Private Data APD_MG, which may in general also be considered
20 as Navigation Data.

STR_VMGI and SFI are the Navigation Data which are directly relevant for the Streamer operation. STR_VMGI includes two kinds of information tables, namely Video Manager Information Management Table (VMGI_MAT) and Play List Search
25 Pointer Table (PL_SRPT), in this order. SFI includes three kinds of information tables, namely Stream File General Information (SF_GI), SOBI Search Pointers #n (SOBI_SRP#n) and all Stream Object Information #n (SOBI#n), in this order.

30 There is no restriction in Stream Recording that each table within Navigation Information must be aligned with a sector boundary.

VMGI_MAT includes information items like end address of Streamer Information (STRI), end address of STR_VMGI, start
35 address of Stream File Information Table (SFIT), start address of Original Program Chain Information (ORG_PGCI) and

start address of User Defined Program Chain Information Table (UD_PGCIT).

PL_SRPT includes information items like Number of Playlist Search Pointers, end address of PL_SRPT, Program Chain numbers of Playlist Information, Playlist Create Time and Primary Text Information.

Stream Object Information General Information (SOBI_GI) includes information items like SOB Type (SOB_TY), SOB Recording Time (SOB_REC_TM), SOB Stream Information Number (SOB_STI_N), Access Unit Data Flags (AUD_FLAGS), SOB Start APAT (SOB_S_APAT), SOB End APAT (SOB_E_APAT), first SOBU of this SOB (SOB_S_SOBU), number of Mapping List entries (MAPL_ENT_Ns).

MAPL_ENT_Ns describes the number of mapping list entries to follow after SOBI_GI.

The purpose of the inventive Mapping List MAPL is to provide all necessary information so that given playlist entries are efficiently translated into disc address pairs, and viceversa.

It is also possible to include Application Private Data which consist of three kinds of information, namely Application Private Data General Information, a set of one or more Application Private Data Search Pointers, and a set of one or more Application Private Data Area. If any Application Private Data exists, these three kinds of information become recorded and stored in this order in the APPLICAT.IFO file.

Stream Data include one or more Stream Objects (SOBs) each of which can be stored as a 'Program stream' as described in ISO/IEC 13818-1, Systems.

A SOB can be terminated by a program_end_code. The value of the SCR field in the first pack of each SOB may be non-zero. A SOB contains the Stream Data packed into a sequence of

'Stream Packs' (S_PCKs). Stream data can be organised as one elementary stream and are carried in PES packets with a stream_id.

- 5 As shown in Fig. 4 a Stream Pack includes a 14-byte pack header and a Stream PES Packet to which a 6-byte PES packet header, a Substream ID byte and a Stream Data Area belongs. The Stream Data Area is headed by a 9-byte Application Header and optionally by an Application Header Extension,
 10 whereby the remaining part is the Application Packet Area. A Stream Object is composed of one or more Stream Packs.

The MAPL table depicted in Fig. 5 contains n pieces or SOBUs. SOBU#1 to SOBU#n of the bitstream to be recorded or of the
 15 recorded bitstream. To SOBU#1 to SOBU#n-1 a corresponding Incremental Application Packet Arrival Time entry IAPAT#1 to IAPAT#n-1 is assigned. DAV denotes a desired address or target address in the bitstream. SOBU#1 to SOBU#n each concern a constant number of bits of the bitstream.

20

As shown in Fig. 6, the Mapping List includes the Initial Time of the MAPL IAPAT#0 and zero or more instances of "Incremental Application Packet Arrival Time" (IAPAT).

	Contents	Number of Bytes
(1) IAPAT	Incremental APAT	2
	Total	2

- 25 The structure of the IAPAT value is depicted in Fig. 9. IAPAT describes the Incremental Application Packet Arrival Time of the corresponding Stream Object Unit in DVD Stream Recording's Incremental PAT Describing Format defined below.

- 30 For an explanation on how to calculate IAPAT(i) during recording, the following notations will be used:

- For abbreviation, M shall denote the number of Mapping List entries MAPL_ENT_Ns.
 - SOBU_S_APAT(i) ($1 \leq i \leq M$) shall denote the start Application Packet Arrival Time of the Stream Object Unit #i of the Stream Object, i.e. the packet arrival time of the first packet belonging to the Stream Object Unit #i. SOBU_S_APAT(1) shall be equal to the Application Time Stamp of the first Application Packet of Stream Object Unit #1 of the Stream Object.
 - IAPAT(0) shall denote the initial value for the Mapping List.
 - IAPAT(i) shall denote the i-th entry of the Mapping List, i.e. IAPAT(0) is the first and IAPAT(M-1) is the last entry of the Mapping List.
 - SUM_IAPAT(i) shall denote the summation of the IAPATs from 0 to i ($i < M$)
- $$\text{SUM_IAPAT}(i) = \text{IAPAT}(0) + \text{IAPAT}(1) + \dots + \text{IAPAT}(i) \quad (\text{eq 1})$$
- with $\text{SUM_IAPAT}(-1) = 0$.
- Then IAPAT(i) shall be chosen such that
- $$\text{IAPAT}(i) = \text{floor}(\text{SOBU_S_APAT}(i+1)/2^{\text{MTU_SHIFT}}) - \text{SUM_IAPAT}(i-1) \quad (\text{eq 2})$$
- for $i = 0, 1, 2, \dots, M-1$.
- The IAPAT value range is limited by the resolution (12 bit) of an IAPAT value and its minimum value ($\text{IAPAT}(i) = 1$ for $i > 0$ and $\text{IAPAT}(0) = 0$):
- $$0 \leq \text{IAPAT}(0) < 2^{12} \quad (\text{eq 3})$$
- and
- $$1 \leq \text{IAPAT}(i) < 2^{12} \quad \text{for } i > 1 \quad (\text{eq 4})$$

The floor function floor(x) rounds down, e.g. floor(1.2) = floor(1.8) = 1, floor(-1.2) = floor(-1.8) = -2.

SOBU_S_APAT(i) is described in the DVD Stream Recording PAT Describing Format. But, in evaluating the equations above

they must be treated as if they were 6 byte unsigned integer values.

Fig. 7 shows, along the time axis, an example of the order of SOBU, SOBU_S_APAT and IAPAT. The left side of the time axis is divided into 'Mapping Time Units' and the right side of the time axis shows the SOBUs.

Mapping Time Unit is a duration corresponding to IAPAT = 1, and can be calculated as

10 Mapping Time Unit = $(2^{(\text{MTU_SHIFT}-9)} / 90000)$ seconds (eq 5)
For MTU_SHFT = 18 bit it corresponds to approx. 5.69 milliseconds.

SOB_S_APAT describes the start Application Packet Arrival Time of a Stream Object, i.e. the packet arrival time of the first packet belonging to the SOB. SOB_S_APAT is described below in the DVD Stream Recording PAT Describing Format: PATs consist of a base part and an extension part. The base part holds the so-called 90kHz unit value, and the extension part holds the less significant value measured in 27MHz units.

(a) Choosing SOB_S_APAT for a new recording

A newly recorded SOB will normally start with the first Application Packet of a SOBU. In this case, SOB_S_APAT and the Application Timestamp of the first Application Packet of the SOB will normally be set to 0.

(b) Calculation of SOB_S_APAT after editing

After editing, e.g. deleting the start of a SOB, SOB_S_APAT, the Application Timestamp of the first Application Packet of the first SOBU of the SOB and the Application Timestamp of the first Application Packet belonging to the SOB may differ and may be not equal to 0.

All possible cases are covered by the following general definition of SOB_S_APAT:

- let ats_e be the 30-bit Application Timestamp of the first Application Packet belonging to the SOB and
- let N be the number of all Application Timestamp wrap-arounds occurring between the 30-bit Application Timestamp of the first Application Packet starting in the first SOBU of the SOB and ats_e , i.e. $0 \leq N \leq 1$, then

SOB_S_APAT[MTU_SHFT + 11...0] = ats_e [MTU_SHFT + 11...0]

SOB_S_APAT[47...MTU_SHFT + 12] = N

- 10 With this definition of SOB_S_APAT, the APAT of the first Application Packet starting in the first SOBU of the SOB is equal to or greater than 0 and less than $2 \text{ MTU_SHIFT} + 12$.

Fig. 10 shows the DVD Stream Recording PAT Describing Format. The variables in this figure are defined as follows:

PAT_base: PAT's base value measured by 90kHz unit

PAT_exten: PAT's extension value measured by 27MHz unit

($0 \leq \text{PAT_exten} < 300$)

PAT in seconds = $(\text{PAT_base}/90000\text{Hz}) + (\text{PAT_exten}/27000000\text{Hz})$

For an unique representation of times, PAT_exten must be in the range of $0 \leq \text{PAT_exten} < 300$. Together, PAT_base and PAT_exten cover a range of more than 1696 hours.

- 25 SOB_E_APAT describes the end Application Packet Arrival Time of the Stream Object, i.e. the packet arrival time of the last packet belonging to the SOB, in the DVD Stream Recording PAT Describing Format. The general definition of SOB_E_APAT is as follows:

- let ats_e be the 30-bit Application Timestamp of the last Application Packet belonging to the SOB and
- let N be the number of all Application Timestamp wrap-arounds occurring between the 30-bit Application Timestamp of the first Application Packet starting in the first SOBU of the SOB and ats_e , i.e. $N \geq 0$, then

$\text{SOB_E_APAT}[\text{MTU_SHFT} + 11 \dots 0] = \text{ats}_e[\text{MTU_SHFT} + 11 \dots 0]$
 $\text{SOB_E_APAT}[47 \dots \text{MTU_SHFT} + 12] = N$

The Application Time Stamp (ATS) in front of each Application packet consists of a 30-bit value. An ATS includes a base part and an extension part. The base part holds the so-called 90kHz unit value, and the extension part holds the less significant value measured in 27MHz units.

Fig. 11 depicts the DVD Stream Recording Application Time Stamp Describing Format. The variables in this figure are defined as follows:

AU_START when set to '1', indicates that the associated Application Packet contains a random access entry point (start of a random access unit) into the stream
 AU_END when set to '1', indicates the associated Application Packet is the last packet of a random access unit
 ATS_base base value of ATS measured in 90kHz units
 ATS_exten extension value of ATS measured in 27MHz units
 $\text{ATS in seconds} = (\text{ATS_base}/90000\text{Hz}) + (\text{ATS_exten}/27000000\text{Hz})$

For a unique representation of times, ATS_exten must be in the range of $0 \leq \text{ATS_exten} < 300$. Together, ATS_base and ATS_exten cover a range of more than 23 seconds.

Fig. 8 depicts the value ranges of ATS, IAPAT and SUM_IAPAT with respect to the 48-bit range of APAT. ATS covers bits 0 to 29. IAPAT covers bits 18 to 29. SUM_IAPAT covers bits 18 to 47.

A significant advantage of the invention is that the mapping list generates timestamps SUM_IAPAT of which the 12 LSB bits No. 18 to 29 are identical to the 12 MSB bits No. 18 to 29 of the stream timestamps ATS. This feature allows to simplify the real-time recorder hardware.

Example function for scanning the Presentation Data until the desired Application Packet is found

The following function describes how to scan Presentation Data in order to retrieve an individual application packet associated with a Packet Arrival Time 'x'. Thereby the Mapping List and the access to it is described in more detail, e.g. internal intermediate values which are required in subsequent steps, see Fig. 5, 6 and 7. The main result of Mapping List access is the Sector offset SOFF, indicating where the scanning starts. The complete scanning will be carried out inside a given SOB.

Notes on nomenclature used:

- x48 is a 6-byte APAT value which is indicated below by '48'.

- The value '30' attached to other variables indicates that they consist of 30 bits, e.g. Application Time Stamp ATS.
- IAPAT(0), IAPAT(1), ... denote the entries of the Mapping List.
- The form var[a...b] denotes the bit field between and including bits a and b of the variable var.
- '[i ... k]' denotes bits i to k of a binary number, i = MSB, k = LSB.
- '/*...*/' denotes explanatory comments.

In order to simplify the example it is assumed that each sector contains an integer number of at least one application packet(s).

Function get_application_packet_location(x48)

- sum_iapat48 = IAPAT(0) * 2^{MTU_SHIFT}; k = 1
- ss48 = IAPAT(k) * 2^{MTU_SHIFT}
- if (sum_iapat48 + ss48)[47...18] ≥ x48[47...18], then go to g)
- sum_iapat48 = sum_iapat48 + ss48
- k = k + 1

```

f) if k < MAPL_ENT_Ns, then go to b)
g) soff = (k-1)*SOBU_SZ                      /* sector
   offset of SOBU#(k) relative to the 1st SOBU of the SOB */
h) offset48[47...30] = sum_iapat48[47...30]
5  i) offset48[29...0] = 0
   j) current_ats30 = 0;
   k) ap_no = 1
      /* Number of AP within Sector, 1 ≤ ap_no ≤ AP_Ns */
   l) previous_ats30 = current_ats30
10  m) current_ats30 = (ATS of the application packet #ap_no of
   sector #soff)
   n) if previous_ats30 is greater than current_ats30, then
      offset48 = offset48 + 230 /*handle ATS wrap around */
   o) if current_ats30 + offset48 = x48 then
15  go to s)                                /* target found! */
   p) if sector #soff contains at least one more application
      packet start, then
      ap_no = ap_no + 1
      go to m)
20  q) soff = soff + 1
   r) go to k)
   s) end of function

```

The desired application packet is now retrieved as packet
 25 #ap_no of sector #soff. A value of ap_no = 1 denotes the
 first Application Packet starting in the Sector. A value of
 soff = 0 denotes the first Sector of the first SOBU of the
 SOB.

30 The above function is a more general example. It can be sim-
 plified if MTU_SHFT < 19. This requirement is fulfilled be-
 cause MTU_SHFT is defined as 18.
 a) sum_iapat30 = IAPAT(0); k = 1

```

b) sum_iapat30 = sum_iapat30 + IAPAT(k)
c) if sum_iapat30 ≥ x48[47...18], then go to f)
d) k = k + 1
e) if k < MAPL_ENT_Ns, then go to b)
5  f) soff = (k-1)*SOBU_SZ                      /* sector off-
      set of SOBU #(k) relative to the 1st SOBU of the SOB */
g) ap_no = 1
      /* number of AP within Sector, 1 ≤ ap_no ≤ AP_PKT_Ns */
h) if (ATS of the application packet #ap_no of sector #soff)
10  equal to x48[29...0], then
      go to l)                                /* target found! */
i) if sector #soff contains at least one more application
      packet start, then
      ap_no = ap_no + 1
15  go to h)
j) soff = soff + 1
k) go to g)
l) end of function

```

20 The desired application packet is now retrieved as packet #ap_no of sector #soff. A value of ap_no = 1 denotes the first Application Packet starting in the Sector. A value of soff = 0 denotes the first Sector of the first SOBU of the SOB.

25 The 30 bits of ATS have the same weight as the 30 LSBs of APAT.

It is not required that the first sector of the first SOBU of a SOB belongs to this SOB. If the first part of a SOB was erased, then the remaining SOB may start in the middle of a
 30 SOBU, i.e. the first sector of this SOBU is not part of the SOB.

In Stream recording, the application performs its own padding, so that the pack length adjustment methods of DVD-ROM

Video or DVD-VR need not to be used. In Stream recording it is safe to assume, that the Stream packets will always have the necessary length..

The data stream also contains application time stamps ATS,
5 e.g. within the data packets.

Claims




1. Method for addressing a bitstream to be recorded or being recorded on a storage medium (STRD), wherein an address table (MAPL) is used that is based on pieces (SOBU#n) of said bitstream, characterised by:
 - said pieces (SOBU#n) each include a constant amount of bits of said bitstream;
 - using a running index (0, 1, 2, 3, ..., n-1), to each address table entry for said pieces, in particular to each address table entry except the one having the highest index, a delta time duration (IAPAT#n) is assigned in said address table;
 - the address table contains in addition an initialisation value (IAPAT#0) which allows to have a share of equal bits between a predetermined amount of MSBs of application time stamps (ATS) and the same amount of LSBs of the summation of said delta time durations (IAPAT#n);
 - in order to get an address value for reaching a target address (DAV) said initialisation value (IAPAT#0) and all delta time durations (IAPAT#1, ... IAPAT#n-1) up to the nearest time duration value corresponding to said address value become accumulated, and the running index (i) corresponding to the delta time duration entry (IAPAT#i) related to said nearest time duration value becomes multiplied by said constant amount in order to compute said address value.
2. Method according to claim 1, wherein said storage medium (STRD) is a Streamer device or a DVD recorder.
3. Method according to claim 1 or 2, wherein said pieces (SOBU#n) of said bitstream contain data packets and a delta time duration value which is the difference between the arrival time of the first packet of a piece and the arrival time of the packet following immediately the last

packet of that piece.




4. Method according to any of claims 1 to 3, wherein the
size of a piece corresponds to the number of bits of an
5 ECC block or a multiple thereof.

5. Method according to any of claims 1 to 4, wherein said
initialisation value corresponds to some, in particular
12, MSBs of the application time stamp (ATS) of the first
10 application packet of the first piece (SOBU) which is de-
scribed by said address table (MAPL).

~~6. Method according to any of claims 1 to 5, wherein said~~
address table is a mapping list (MAPL).



2/4

**Fig.4****Fig.5****Fig.6**




Fig.8




Fig.9






Fig.7

4/4

**Fig.10****Fig.11**

INTERNATIONAL SEARCH REPORT

Int. l. Application No

PCT/EP 99/06377

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 G11B27/32 G11B20/12 G11B27/10

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 G11B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP 0 797 204 A (PIONEER ELECTRONIC CORP) 24 September 1997 (1997-09-24) * page 2, line 28 - page 3, line 4; page 12, line 25-42; page 18, line 31-49; figure 5 *	1,2,4
A	FR 2 759 471 A (SONY CORP) 14 August 1998 (1998-08-14) * page 11, line 22 - page 12, line 25; page 21, line 21 - page 25, line 12 *	1,2,4
A	EP 0 729 153 A (HITACHI LTD) 28 August 1996 (1996-08-28) column 3, line 45 -column 4, line 13; figure 2	1,2

	--- -/--	



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

13 December 1999

Date of mailing of the international search report

21/12/1999

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Mourik, J

INTERNATIONAL SEARCH REPORT

Int ional Application No

PCT/EP 99/06377

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP 0 673 034 A (SONY CORP) 20 September 1995 (1995-09-20) page 25, line 13 -page 28, line 4; figures 34-40	1,2
A	US 5 630 005 A (ORT JEFFREY) 13 May 1997 (1997-05-13) claim 1	1,2

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/EP 99/06377

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
EP 0797204	A	24-09-1997	JP 9251763 A	22-09-1997
FR 2759471	A	14-08-1998	JP 10222316 A	21-08-1998
EP 0729153	A	28-08-1996	JP 8235833 A	13-09-1996
			CN 1135072 A	06-11-1996
			CN 1229235 A	22-09-1999
			EP 0930618 A	21-07-1999
EP 0673034	A	20-09-1995	AU 681259 B	21-08-1997
			AU 1824595 A	18-09-1995
			BR 9505853 A	21-02-1996
			CA 2160913 A	08-09-1995
			CN 1115076 A	17-01-1996
			CN 1124062 A	05-06-1996
			EP 0696799 A	14-02-1996
			JP 7311950 A	28-11-1995
			WO 9524037 A	08-09-1995
			PL 311310 A	05-02-1996
			SG 24104 A	10-02-1996
			US 5734787 A	31-03-1998
			US 5592450 A	07-01-1997
			US 5596565 A	21-01-1997
			US 5745505 A	28-04-1998
US 5630005	A	13-05-1997	NONE	

THIS PAGE BLANK (USPTO)